

**339G GODIVA GRAND**



**OVERALL DIMENSIONS:**

					
32	25	23.5	19	n/a	<b>INCHES</b>

DIMENSIONS ARE APPROXIMATE

**YARDAGE:**

COM: (2.5 yards each – based on plain, non-directional, no repeat textile)

**1339 GODIVA BAR**



**OVERALL DIMENSIONS:**

					
44	22	20.5	30.5	n/a	<b>INCHES</b>

DIMENSIONS ARE APPROXIMATE

**YARDAGE:**

COM: (2.25 yards each – based on plain, non-directional, no repeat textile)

**SPECIFICATION:**

- Frame shall be constructed from solid kiln dried hardwood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Chair - Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 7/8" x 1 7/8" tapering to 1" x 1" at bottom.  
Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 3/4" x 2 1/4" and tapers to the bottom.
- Barstool - Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 1/2" x 1 1/2" tapering to 1 1/4" x 1 1/4" at bottom.  
Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 1/2" x 2" and tapers to 1 1/4" x 1 1/2" at bottom.

46 Dufflaw Road Toronto ON M6A 2W1 | 416-782-9100 | 1-800-881-3928 | www.havaseat.com | isa@havaseat.com



- The seat rails are made from single stock lumber 2" x 3" and shaped to conform to the chair design and are glued dowelled and screwed together with corner blocks.
- The seat shall be  $\frac{3}{4}$ " thick solid core ply and applied to the solid hardwood frame. The seat is attached to the hardwood frame and screwed to the frame.
- The curved back is a single piece formed plywood screwed into the seat frame.
- Foam is 2" high density CAL TB117-2013 foam on the seat and  $\frac{1}{2}$ " on the inside and outside back.