

**490-82 SUKI STACK**

---



**OVERALL DIMENSIONS:**



33.5    20.5    19    n/a    INCHES

DIMENSIONS ARE APPROXIMATE

**YARDAGE:**

*COM: 1 yard per every 2 chairs (based on plain, non-directional, no repeat textile)*

**491-82 SUKI ARM STACK**

---



**OVERALL DIMENSIONS:**



33.5    20.5    23    26    INCHES

DIMENSIONS ARE APPROXIMATE

**YARDAGE:**

*COM: 1 yard per every 2 chairs (based on plain, non-directional, no repeat textile)*

**1490-82 SUKI BARSTOOL**

---



**OVERALL DIMENSIONS:**



42    20.5    17.5    29    n/a    INCHES

DIMENSIONS ARE APPROXIMATE

**YARDAGE:**

*COM: 1 yard per every 2 chairs (based on plain, non-directional, no repeat textile)*



#### SPECIFICATION:

- Frame to be constructed from solid kiln dried beechwood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 $\frac{3}{4}$ " x 1 $\frac{3}{4}$ " tapering to 1" x 1" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 $\frac{1}{2}$ " x 1 $\frac{1}{2}$ " and tapers at the bottom 1"x 1 $\frac{1}{4}$ ".
- Front and rear legs and attached by a solid beech frame that is 2 $\frac{1}{2}$ " x 1 $\frac{3}{4}$ ".
- Side stretchers run front to back leg and are dowelled and glued together.
- The chair frame and seat frame are connected together by dowels, corner blocks, bolts and glue.
- The seat shall be  $\frac{1}{2}$ " thick solid core ply and applied to the solid beech frame. The seat is attached to the beech frame via screws. Foam and upholstery are applied after assembly.
- Plywood back is curved  $\frac{1}{2}$ " thick beech that is glued & doweled to the back upright.