

490-89 GLEE STACK



OVERALL DIMENSIONS:



33.5 20.5 19 n/a INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 1.5 yards per chair (based on plain, non-directional, no repeat textile)

491-89 GLEE ARM STACK



OVERALL DIMENSIONS:



33.5 20.5 23 26 INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 1.5 yards per chair (based on plain, non-directional, no repeat textile)

1490-89 GLEE BARSTOOL



OVERALL DIMENSIONS:



42 20.5 17.5 29 n/a INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 1.5 yards per chair (based on plain, non-directional, no repeat textile)



SPECIFICATION:

- Frame to be constructed from solid kiln dried beechwood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 $\frac{3}{4}$ " x 1 $\frac{3}{4}$ " tapering to 1" x 1" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 $\frac{1}{2}$ " x 1 $\frac{1}{2}$ " and tapers at the bottom 1"x 1 $\frac{1}{4}$ ".
- Front and rear legs and attached by a solid beech frame that is 2 $\frac{1}{2}$ " x 1"
- 3/4" x 7/8" stretchers are dowelled and glued to legs.
- The frame and seat frame are connected together by dowels, corner blocks, bolts and glue.
- The seat shall be 1/2" thick solid core ply and applied to the solid beech frame. The seat is attached to the beech frame via screws. Foam and upholstery are applied after assembly.
- Plywood back is curved 1/2" thick beech that is glued & doweled to the back upright.