

1328 TONIC BAR



OVERALL DIMENSIONS:



37.5 21.5 18 n/a INCHES

YARDAGE:

COM: 1.5 yards per chair (based on based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Stool frame shall be constructed from solid kiln dried beech. Lumber to be dried to a final moisture content between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1³/₄"x1³/₄" tapering to 1" x 1" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1¹/₂" x 1¹/₂" and tapers at the top 1¹/₄" x 1" and bottom 1" x 1¹/₄".
- Front and rear legs and attached by a solid beech frame that is 2¹/₂" x 1³/₄".
- Side stretchers run front to back leg and are dowelled and glued together. Front and back stretchers run side to side and are dowelled and glued together.
- The barstool frame and seat frame are connected together by dowels, corner blocks, bolts and adhesive.
- The seat shall be 1/2" thick solid core ply with webbing and applied to the solid beech frame. The seat is attached to the beech frame via screws. High density CAL 117 FR foam and upholstery are applied after assembly.
- Aluminum foot guards can be attached to wood stretchers on the barstool model.
- Also available in counter stool at 24" seat height.