

205-WS TAVERN SIDE CHAIR



OVERALL DIMENSIONS:



30.5 19 21.5 18 n/a INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 3/4 yards for every 02 chairs (based on based on plain, non-directional, no repeat textile)

201-WS TAVERN ARM CHAIR



OVERALL DIMENSIONS:



30.5 19 21.5 18 28 INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 3/4 yards for every 02 chairs (based on based on plain, non-directional, no repeat textile)

1201 TAVERN BAR STOOL



OVERALL DIMENSIONS:



45 19 21.5 31 43 INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 3/4 yards for every 02 chairs (based on based on plain, non-directional, no repeat textile)



SPECIFICATION:

- Chair frame and all exposed wood is constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg are approx. 1 3/8" tapering to 1 1/8" at bottom of Chair; AND 1 5/8" tapering to 1" at bottom of Barstool.
- Rear legs to be constructed from single stock lumber. Finished dimensions at the top of the leg are approx. 1 3/8" tapering to 1 1/8" at bottom of Chair, AND 1 1/4" tapering to 1" at bottom of Barstool.
- Seat shall be 1/2" thick solid core beech wood ply and applied to the solid beech wood frame.
- Backrest stretchers are built of steamed bent wood, glued by way of mortise and tenon into the solid wood back rail and seat
- "U" type stretchers are screwed onto the front and back legs, and between the seat and back for added strength.
- The chair frame and seat frame are connected together by dowels, bolts and glue.
- All exposed wood to be finished in any standard ISA wood finish and receive a clear urethane coat, low-gloss, for added protection.
- Available in Wood Seat (WS) and with Upholstered Seat Pad (USP).
- All styles include nail-in nylon glides.