


445 MOSCATO SIDE CHAIR



OVERALL DIMENSIONS:




YARDAGE:

COM: 1.75 YARDS per chair (based on based on plain, non-directional, no repeat textile)

446 MOSCATO ARM SIDE CHAIR



OVERALL DIMENSIONS:



YARDAGE:

COM: 2 YARDS per chair (based on based on plain, non-directional, no repeat textile)

1445 MOSCATO BAR



OVERALL DIMENSIONS:




YARDAGE:

COM: 1.75 YARDS per chair (based on based on plain, non-directional, no repeat textile)

1446 MOSCATO ARM BAR



OVERALL DIMENSIONS:



YARDAGE:

COM: 2 YARDS per chair (based on based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Frame shall be constructed from solid ash. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 2" x 3/4" tapering to 1 1/4" x 3/4" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 2" x 1 1/4" and tapers to the bottom.
- The seat rails are made from single stock lumber 2" x 2 1/4" and shaped to conform to the chair design and are glued dowelled and screwed together with corner blocks.
- The seat shall be 1/2" thick solid core ply with webbing and applied to the solid oak hardwood frame. The seat is attached and screwed to the hardwood frame.
- The curved back is made of single piece formed plywood screwed into the seat frame.
- 3/4" high density CAL 117 FR foam and Dacron wrap is applied to the seat, 1/2" thick foam on the inside back and 1/4" thick foam on the outside back.