

479 MONTAUK SIDE CHAIR



OVERALL DIMENSIONS:



32 21 19 19 INCHES

*DIMENSIONS ARE APPROXIMATE AND MAY VARY SLIGHTLY.

COM YARDAGE:

1.75 yard for every 03 chairs (based on no repeat, non-directional material)

SPECIFICATION:

- Frames are constructed of solid kiln dried ash wood. Lumber to be dried to a final moisture content level between 6% - 8%.
- The frames are connected together by mortise and tenon, corner blocks, screws and glue. They also receive reinforcing stretchers, in solid wood
- Legs are 2" x 1 1/4" at the top, tapering down to 1" x 1 1/4" at the bottom. They connect at the top via an X-brace structure.
- The back rest consists of 1/2" thick bent plywood and is attached to the main metal back bracket via screws. Plywood is stained per selected finish.
- Metal bracket is 3/4" diameter and can be finished in any ISA powder coat/plated finish.
- The seat consists of 1/2" thick plywood, with a high-density foam seat, 2.5" thick, meeting CAL 117 FR. Upholstery is then applied as specified. Tufting is standard, as shown.
- All exposed wood is finished in any standard ISA wood finish. Frames then receive a clear urethane top coat in low gloss for added protection.
- All items include nail-in nylon glides suitable for most flooring types.